


# H-Type® Heavy-Duty Primary Cleaner

## High Efficiency Tungsten-Carbide Primary Cleaner

The H-Type® conveyor belt cleaner from Flexco is designed to be positioned on the head pulley and to remove the bulk of the carryback from the belt. Proven performance for over 25 years as the most efficient primary cleaner in material handling applications such as coal, iron ore, bauxite, and hard rock mining.



### Features and Benefits

- Works on reversing belts
- Available in power coated or stainless steel
- Optional Compression Spring Tensioner maintains uniform, constant blade tension to belt. Provides a quick visual check to ensure tension is correct
- Optional J-Bolt Tension Mounting Kit, allows for easy and quick tension adjustment
- Also available with long wearing polyurethane blades for use in mechanically spliced applications
- Also available in FRAS for underground coal applications

# H-Type® Heavy-Duty Primary Cleaner

**Maximum Belt Speed**  
6 M/sec

**Temperature Rating**  
-35° C to 82° C

**Usable Blade Wear Length**  
9 mm

**Blade Material**  
Impact resistant, long-lasting tungsten carbide

**Available for Belt Widths**  
600 to 3000 mm

## H-Type® Belt Cleaner with V-Tips

V-Tips should ONLY be used on vulcanised belts. Suspension arm size is determined by head pulley diameter (over lagging and belt). See chart below.

## H-Type® Belt Cleaner with XF2-Tips

XF2 Tips are recommended for mechanically spliced belts but are also suitable for vulcanised belts. XF2 Tip size is determined by head pulley diameter (see chart below). Spring Tensioners are standard on HXF cleaners.

Pole Specifications		
Belt Width	Pole Length	Pole Diameter
mm	mm	mm
450	1250	60
600	1350	60
750	1500	60
900	1650	60
1050	1800	60
1200	1950	60
1500	2350	73
1600	2450	73
1800	2650	73

Additional sizes up to 3,000 mm available upon request.

Arm Selection Chart	
Head Pulley Dia. + Belt + Lagging (mm)	Arm Size
500-799	CS
800-999	CM
1000-1199	CL
1200-1700	CLL

## Ordering Information

H-Type with V-Tips Mild Steel			
Belt Width mm	Suspension Arm Size	Ordering Number	Item Code
450	SS	HV450SS	73026
	S	HV450S	73028
	M	HV450M	73019
600	SS	HV600SS	73045
	S	HV600S	73030
	M	HV600M	73173
750	SS	HV750SS	73053
	S	HV750S	73032
	M	HV750M	73174
900	SS	HV900SS	73055
	S	HV900S	73034
	M	HV900M	73175
1050	L	HV900L	73178
	SS	HV1050SS	73057
	S	HV1050S	73056
1050	M	HV1050M	73036
	L	HV1050L	73179
	1200	SS	HV1200SS
S		HV1200S	73058
M		HV1200M	73038
1200	L	HV1200L	73180
	M	HV1500M	73177
	1500	L	HV1500L
LL		HV1500LL	73215
1600		M	HV1600M
	L	HV1600L	73638
	LL	HV1600LL	73639
1800	M	HVHD1800M	74602
	L	HVHD1800L	74477
	LL	HVHD1800LL	74478
2100	M	HVHD2100M	74539
	L	HVHD2100L	74540
	LL	HVHD2100LL	74541
2400	M	HVHD2400M	74544
	L	HVHD2400L	74545
	LL	HVHD2400LL	74546
2600	M	HVHD2600M	A2396
	L	HVHD2600L	A2461
	LL	HVHD2600LL	A2397
3000	M	HVHD3000M	74591
	L	HVHD3000L	74592
	LL	HVHD3000LL	74593

H-Type with V-Tips and PCST Tensioner - Mild Steel				
Belt Width mm	Suspension Arm Size	Ordering Number	Item Code	
450	SS	HV450SS-PCST	63936	
	S	HV450S-PCST	63937	
	M	HV450M-PCST	63938	
600	SS	HV600SS-PCST	63939	
	S	HV600S-PCST	63940	
	M	HV600M-PCST	63941	
750	SS	HV750SS-PCST	63942	
	S	HV750S-PCST	63943	
	M	HV750M-PCST	63944	
900	SS	HV900SS-PCST	63945	
	S	HV900S-PCST	63946	
	M	HV900M-PCST	63947	
900	L	HV900L-PCST	63948	
	1050	SS	HV1050SS-PCST	64045
		S	HV1050S-PCST	63950
M		HV1050M-PCST	63951	
1050	L	HV1050L-PCST	63952	
	1200	SS	HV1200SS-PCST	63953
		S	HV1200S-PCST	63954
M		HV1200M-PCST	63955	
1200	L	HV1200L-PCST	63956	
	1500	M	HV1500M-PCST	63957
		L	HV1500L-PCST	63958
LL		HV1500LL-PCST	63959	
1600	M	HV1600M-PCST	63960	
	L	HV1600L-PCST	63961	
	LL	HV1600LL-PCST	63962	
1800	M	HV1800M-PCST	63963	
	L	HV1800L-PCST	63964	
	LL	HV1800LL-PCST	63965	
2100	M	HV2100M-PCST	63966	
	L	HV2100L-PCST	63967	
	LL	HV2100LL-PCST	63968	
2400	M	HV2400M-PCST	63969	
	L	HV2400L-PCST	63970	
	LL	HV2400LL-PCST	63971	
2600	M	HV2600M-PCST	63972	
	L	HV2600L-PCST	63973	
	LL	HV2600LL-PCST	63974	
3000	M	HV3000M-PCST	63975	
	L	HV3000L-PCST	63976	
	LL	HV3000LL-PCST	63977	

Contact Flexco for further blade and tensioner options.  
Also available in Stainless Steel.

Authorized Distributor:

Flexco (Aust.) Pty. Ltd • 10 Solent Circuit • Baulkham Hills NSW 2153 • Australia  
Tel: 612-8818-2000 • Fax: 612-8824-6333 • E-mail: salesau@flexco.com

Visit [www.flexco.com](http://www.flexco.com) for other Flexco locations and products.

©2016 Flexible Steel Lacing Company. 01/16. For reorder: X4103

